according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 1 of 11

#### 1. Identification

## **Product identifier**

**AESUB** green

## Recommended use of the chemical and restrictions on use

#### Use of the substance/mixture

Coatings

## Details of the supplier of the safety data sheet

Company name: Scanningspray Vertriebs GmbH

Street: Johann-Strauss-Str. 13
Place: D-45657 Recklinghausen
Telephone: +49 (0)176 82 41 39 36
e-mail: info@aesub.com

Contact person: Max Liese Telephone: +49(0)231-5868 9271

e-mail: liese@aesub.com Internet: www.aesub.com

**Emergency phone number:** 24 Hour Emergency Contact Phone Number for Chemichal Emergency, Spill,

Leak, Fire, Exposure or Accident. Call Day and Night within USA and Canada:

1-800-424-9300, outside USA and Canada: 001-703-527-3887

#### **Further Information**

Emergency phone number China: 4001-204937

(CCN 994267 / WISAG FMO Cargo Service GmbH & Co. KG)

### 2. Hazard(s) identification

#### Classification of the chemical

### 29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 2 Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2A

Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

### **Label elements**

#### 29 CFR Part 1910.1200

Signal word: Danger

Pictograms:







# **Hazard statements**

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

#### **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 2 of 11

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If on skin: Wash with plenty of Water and soap.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use Sand, Carbon dioxide (CO2), Extinguishing powder to extinguish.

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

#### Hazards not otherwise classified

No information available.

### 3. Composition/information on ingredients

## **Mixtures**

#### Hazardous components

CAS No	Components	Quantity
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	50 %
64-17-5	ethanol; ethyl alcohol	28.7 %
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	11.04 %

#### 4. First-aid measures

#### **Description of first aid measures**

#### **General information**

When in doubt or if symptoms are observed, get medical advice. Remove victim out of the danger area. Do not leave affected person unattended. Remove contaminated, saturated clothing immediately.

#### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

# After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 3 of 11

mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

#### Most important symptoms and effects, both acute and delayed

Narcotic effects

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### 5. Fire-fighting measures

#### **Extinguishing media**

#### Suitable extinguishing media

Water spray, BC-powder

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

Water

#### Specific hazards arising from the chemical

Highly flammable. Vapours are heavier than air, spread along floors and form explosive mixtures with air. In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, Pyrolysis products, toxic.

#### Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance.

#### Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Supress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fume/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

# **Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

Retain contaminated washing water and dispose it.

### Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

# 7. Handling and storage

#### Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapors may form explosive mixtures with air.

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 4 of 11

## Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

## Further information on storage conditions

Provide earthing of containers, equipment, pumps and ventilation facilities.

# 8. Exposure controls/personal protection

### **Control parameters**

#### **Exposure limits**

CAS No.	Substance	ppm	mg/m³	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	PEL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
67-63-0	2-Propanol	200			TWA (8 h)	ACGIH-2020
		400			STEL (15 min)	ACGIH-2020
-	C5 - C6 Alkanes		1500		TWA (8 h)	ACGIH-2020
-	C5 - C6 Cycloalkanes		1500		TWA (8 h)	ACGIH-2020
-	C7 - C8 Alkanes		1500		TWA (8 h)	ACGIH-2020
-	C7 - C8 Cycloalkanes		1500		TWA (8 h)	ACGIH-2020
64-17-5	Ethanol	1000			STEL (15 min)	ACGIH-2020
64-17-5	Ethyl alcohol (Ethanol)	1000	1900		TWA (8 h)	PEL
64-17-5	Ethyl alcohol	1000	1900		TWA (8 h)	REL
67-63-0	Isopropyl alcohol	400	980		TWA (8 h)	PEL
		400	980		TWA (8 h)	REL
		500	1225		STEL (15 min)	REL
78-93-3	Methyl ethyl ketone	200			TWA (8 h)	ACGIH-2020
		300			STEL (15 min)	ACGIH-2020

# **Biological Exposure Indices (BEI-ACGIH)**

CAS No.	Substance	Determinant	Value	Test material	Sampling time
67-63-0	2-PROPANOL	Acetone	40 mg/L		End of shift at end of workweek
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

#### **Exposure controls**

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 5 of 11











#### Appropriate engineering controls

Provide adequate ventilation.

#### Protective and hygiene measures

Do not breathe gas/fume/vapour/spray. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

Butyl caoutchouc (butyl rubber). Thickness of glove material: 0,7 mm ,penetration time (maximum wearing period): 240min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: ABEK-P2

#### **Environmental exposure controls**

Avoid release to the environment.

# 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state: Liquid
Color: colorless
Odor: like: Camphor
Odour threshold: not determined

pH-Value: not determined

## Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

58 °C

boiling range:

Flash point: < - 29 °C

Flammability

Solid: not applicable
Gas: not applicable

#### **Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 13,5 vol. %
Auto-ignition temperature: 225 °C

Self-ignition temperature

Solid: not applicable

according to 29 CFR 1910.1200(g)

**AESUB** green

Revision date: 02.06.2021 Page 6 of 11

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

The product is not: oxidising.

Vapor pressure:250 hPaDensity:0,7 - 0,72 g/cm³Water solubility:not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Viscosity / dynamic:

Viscosity / kinematic:

Relative vapour density:

Evaporation rate:

not determined

not determined

not determined

Other information

No information available.

## 10. Stability and reactivity

### Reactivity

Highly flammable.

# **Chemical stability**

Stability: Stable

The product is stable under storage at normal ambient temperatures.

#### Possibility of hazardous reactions

Hazardous reactions: Will not occur

No known hazardous reactions.

### **Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapors may form explosive mixtures with air.

# **Incompatible materials**

Oxidising agent

# **Hazardous decomposition products**

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, Pyrolysis products, toxic.

## 11. Toxicological information

## Information on toxicological effects

#### Route(s) of Entry

Eye contact, oral, dermal, inhalative.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 7 of 11

CAS No	Components							
	Exposure route	Dose		Species	Source	Method		
64-17-5	ethanol; ethyl alcohol							
		LD50 10 mg/kg	0170	Rat	Manufacturer			

# Irritation and corrosivity

Causes skin irritation

Causes serious eye irritation

#### Sensitizing effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha)

# Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (IARC): Ethanol in alcoholic beverages (CAS 64-17-5) is listed in group 1. Isopropyl

alcohol (CAS 67-63-0) is listed in group 3.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways

# **Practical experience**

# Other observations

No information available.

# 12. Ecological information

### **Ecotoxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Components								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
64-17-5	ethanol; ethyl alcohol								
	Acute fish toxicity	LC50 mg/l	15400	96 h	Piscis	Manufacturer			
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Algae	Manufacturer			

#### Persistence and degradability

The product has not been tested.

# **Bioaccumulative potential**

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Components	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,77
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

## **Mobility in soil**

The product has not been tested.

### Other adverse effects

No information available.

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 8 of 11

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### 13. Disposal considerations

#### Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

## Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

# 14. Transport information

#### **US DOT 49 CFR 172.101**

UN/ID number: UN 1993

Proper shipping name: FLAMMABLE LIQUIDS, N.O.S. (ethanol; ethyl alcohol, Naphtha

(petroleum), hydrotreated light; Low boiling point hydrogen treated

naphtha)

Transport hazard class(es):

Packing group:

Hazard label:

3



### Marine transport (IMDG)

UN number: UN 1993

**UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.(ethanol; ethyl alcohol, Naphtha (petroleum),

hydrotreated light; Low boiling point hydrogen treated naphtha)

Transport hazard class(es):3Packing group:IIHazard label:3



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

# Air transport (ICAO-TI/IATA-DGR)

UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethanol; ethyl alcohol, Naphtha

(petroleum), hydrotreated light; Low boiling point hydrogen treated

naphtha)

Transport hazard class(es):

Packing group:

Hazard label:

3

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 9 of 11



Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

**Environmental hazards** 

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen

treated naphtha

#### Special precautions for user

Warning: Combustible liquid.

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# 15. Regulatory information

# **U.S. Regulations**

#### **National Inventory TSCA**

CAS No. 64742-49-0 (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha):

CAS No. 64-17-5 (ethanol; ethyl alcohol): Yes.

CAS No. 67-63-0 (propan-2-ol; isopropyl alcohol; isopropanol): Yes.

CAS No. 78-93-3 (butanone; ethyl methyl ketone): Yes.

#### **National regulatory information**

SARA Section 304 CERCLA:

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (64742-49-0): Fire hazard, Immediate (acute) health hazard

ethanol; ethyl alcohol (64-17-5): Fire hazard, Immediate (acute) health hazard

Isopropyl alcohol (mfg-strong acid process) (67-63-0): Fire hazard, Immediate (acute) health hazard Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:

Isopropyl alcohol (mfg-strong acid process) (67-63-0): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Methyl ethyl ketone (78-93-3)

# State Regulations

#### Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

#### 16. Other information

according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 10 of 11

#### **Hazardous Materials Information Label (HMIS)**

Health: 2
Flammability: 4
Physical Hazard: 1

#### **NFPA Hazard Ratings**

Health: 2
Flammability: 4
Reactivity: 1

Unique Hazard:

Revision date: 02.06.2021

Revision No: 1,1

### Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

CFR: Code of Federal Regulations DOT: Department of Transportation

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IARC: International Agency for Research on Cancer

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: permissible exposure limit REL: recommended exposure limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term exposure limit TSCA: Toxic Substances Control Act

TWA: time-weighted average TI: Technical Instructions

DGR: Dangerous Goods Regulations

**UN: United Nations** 

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds

#### Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.



according to 29 CFR 1910.1200(g)

# **AESUB** green

Revision date: 02.06.2021 Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)